

Av. Ricardo Balbin Nº7015 (diag. 101) Ex Ruta 8 Loma Hermosa - San Martín - Bs. As. Tel/Fax: 4769-3266 Email: kuplack@kuplack.com.ar MSN: kuplack@hotmail.com



# **Benefits**

- · Economical, medium textured ceiling panel has upscale appearance.
- CLIMAPLUS<sup>™</sup> 15-year Lifetime System Warranty to withstand conditions up to 104 °F (40°C)/ 90% relative humidity without visible sag when used with USG's Donn® Brand Suspension Systems.

#### **Applications**

- Schools
- Corridors
- · General offices
- · Retail stores

Pebbled CLIMAPLUS™ Panels/Donn Brand DX®/DXL™ Suspension System

# **Acoustical Ceilings**

# $\begin{array}{c} \textbf{Pebbled} \\ \textbf{\textit{ClimaPlus}} \\ \end{array}$

| CLIMAPLUS"           |                              |            |                 |                 |      | (N) UL C | assified     |     |       |  |                 |                                  |               |
|----------------------|------------------------------|------------|-----------------|-----------------|------|----------|--------------|-----|-------|--|-----------------|----------------------------------|---------------|
| NON-SAG<br>WARRANTY  | Edge                         | Panel Size |                 | Class Item No.  |      | NRC      | CAC LR¹ Min. |     | Color |  | Grid<br>Options | Recycled<br>Content <sup>2</sup> | Panel<br>Cost |
|                      |                              | 2′x4       | Y <b>x5/8</b> ″ | Class A         | 4800 | .55      | 35           |     | White |  | A, B            | 30%                              | \$            |
|                      | (SLT) <b>2</b> ′ <b>x2</b> ′ |            | 2′x5/8″         | Class A 480     | 4805 | .55      | 35           | .87 | White |  | D               | 30%                              | \$            |
|                      | (FLB)                        | 2′x2       | 2′x5/8″         | Class A         | 4867 | .55      | 35           | .87 | White |  | E, F, G         | 30%                              | \$            |
|                      |                              |            |                 | C<br>CENTRICITE | E™   |          |              |     |       |  |                 |                                  |               |
| Grid Profile Options |                              |            |                 |                 |      |          |              |     |       |  |                 |                                  |               |

ASTM E1264 classification Type III, Form 2, Pattern CE ASTM E84 surface burning characteristics

Class A Flame spread: 25 Smoke developed: 10 Weight 0.72 lb./ft.² Thermal resistance R-1.4 Maximum backloading See Warranty for details. Maintenance

Can be cleaned easily with a soft brush or vacuum.

## Footnotes

LR values are shown
as averages.
For details, see the Recycled
Content selector.

## SAFETY FIRST!

Follow good safety practices. Read material safety data sheets and related literature on products before specification and/or installation.

